


		PIN	Symbol
21	B3	1	LEDA
22	B4	2	LEDK
23	G0	3	VCC
24	G1	4	GND
25	G2	5	D0N
26	G3	6	D0P
27	G4	7	GND
28	G5	8	CLKN
29	R0	9	CLKP
30	R1	10	GND
31	R2	11	D1P
32	R3	12	D1N
33	R4	13	GND
34	RESET	14	VSYNC
35	CS	15	HSYNC
36	SCL	16	PCLK
37	SDA	17	DE
38	IM0	18	B0
39	IM1	19	B1
40	IM2	20	B2

IM0-2 101 MIPI

Backlight circuit



Vf=19.2V±1.8V  
If=20mA

SPECIFICATIONS:

- 1. DRIVE IC: ST7701S
- 2. DISPLAY TYPE: 3.0" / IPS
- 3. OPERATING TEMPERATURE: -20 ~ 70°C
- 4. STORAGE TEMPERATURE: -30 ~ 80°C
- 5. VIEWING ANGLE: ALL
- 6. BACKLIGHT: 6 LED/SERIES/20mA
- 7. CUSTOMER PART NO.: BOCEN STANDERD PRODUCT

BOCEN DISPLAY TECHNOLOGY CO., LTD.

DESIGNED BY: Shawn	<b>BF3040-01</b>	VERSION: 1.0
CHECKED BY: William		NO.: 1 OF 1
APPROVED BY: Rio		UNIT: mm

Website: <http://www.bocentech.com>

DATE: 2021-10-18