

FPC弯折后客户参考图

展开出货

PIN	SYMBOL
1	X(L)
2	Y(U)
3	X(R)
4	Y(D)
5	GND
6	IOVCC(1.8V/2.8V)
7	VCI(2.8)
8	FMARK
9	CS/SPI CS
10	RS/A0(4 WIRE)
11	WR/SPI SCL/SCK
12	RD
13	SPI SDI/SDA
14	SPI SDO
15	RESET
16	GND
17	D0
18	D1
19	D2
20	D3
21	D4
22	D5
23	D6
24	D7
25	D8
26	D9
27	D10
28	D11
29	D12
30	D13
31	D14
32	D15
33	A
34	K
35	K
36	K
37	GND
38	IMO
39	IM1
40	IM2

SPECIFICATIONS:

- 1. DISPLAY TYPE: 3.5"/ TN / HVGA 320*480
- 2. DRIVE IC: ILI9488
- 3. OPERATING TEMPERATURE: -20 ~ 70°C
- 4. STORAGE TEMPERATURE: -30 ~ 80°C
- 5. VIEWING ANGLE: 12 O'CLOCK
- 6. BACKLIGHT: 6 WHITE LED, 90mA
- 7. CUSTOMER PART NO.: BOCEN STANDARD PRODUCT


BOCEN DISPLAY TECHNOLOGY CO., LTD.

DESIGNED BY: Shawn

BF3540-01R

VERSION: 1.0

CHECKED BY: William



NO.: 1 OF 1

APPROVED BY: Rio

UNIT: mm

Website: <http://www.bocentech.com>

DATE: 2018-9-20