



PIN	Symbol
1	LED K
2	LED A
3	GND
4	VDD
5	R0
6	R1
7	R2
8	R3
9	R4
10	R5
11	R6
12	R7
13	G0
14	G1
15	G2
16	G3
17	G4
18	G5
19	G6
20	G7
21	B0
22	B1
23	B2
24	B3
25	B4
26	B5
27	B6
28	B7
29	GND
30	DCLK
31	DISP
32	NC
33	NC
34	DE
35	NC
36	GND
37	NC
38	NC
39	NC
40	NC

Note:

1. General Tolerance  $\pm 0.30\text{mm}$
2. FPC Connector Suggestion "FH19SC-40S-0.5SH"

背光电路:



BOCEN DISPLAY TECHNOLOGY CO., LTD.

DISPLAY TYPE:	5.0" TFT(Anti-Glare)	INTERFACE:	Digital	PIXEL PITCH:	0.077 X 0.231 mm
POLARIZER MODE:	Normally White Transmissive	OPERATING TEMP:	-20°C TO +70°C	BACK LIGHT:	LED WHITE(X14), 7串*2并
VIEWING DIRECTION:	6 O'CLOCK	STORAGE TEMP:	-30°C TO +80°C		
Dot matrix:	480(RGB)X272 DOTS	STRUCTURE:	LCD+IC+FPC+BL	MATERIAL NOTE	ROHS REQUEST

DESIGNED BY: Shawn	<b>BF5040-01</b>	VERSION: 1.0
CHECKED BY: William		NO.: 1 OF 1
APPROVED BY: Rio		UNIT: mm
Website: <a href="http://www.bocentech.com">http://www.bocentech.com</a>		DATE: 2019-7-25