

PIN	SYMBOL
1	FG
2	VSS
3	VDD(5V)
4	V0
5	/WR
6	/RD
7	/CE
8	C/D
9	RST
10	DB0
11	DB1
12	DB2
13	DB3
14	DB4
15	DB5
16	DB6
17	DB7
18	FS
19	LED-A(5V)
20	LED-K

SPECIFICATIONS:

- | | |
|---------------------------|--|
| 1. DISPLAY TYPE: | STN / POSITIVE (YELLOW-GREEN) / TRANSMISSIVE |
| 2. DRIVE IC: | ICB-UCI6963/LQFP67 or EQV. |
| 3. CONNECTOR: | ZEBRA |
| 4. OPERATING VOLTAGE: | VOP = 9.0 V, VDD = 5.0V |
| 5. OPERATING TEMPERATURE: | -20 ~ 70°C |
| 6. STORAGE TEMPERATURE: | -30 ~ 80°C |
| 7. DRIVE MODE: | 1/64 DUTY, 1/9 BIAS |
| 8. VIEWING ANGLE: | 6 O'CLOCK |
| 9. BACKLIGHT: | YELLOW-GREEN LED, I = 80mA |
| 10. CUSTOMER PART NO.: | BOCEN STANDARD PRODUCT |


BOCEN DISPLAY TECHNOLOGY CO., LTD.

DESIGNED BY: Shawn

BB12864-06

VERSION: 1.0

CHECKED BY: William



NO.: 1 OF 1

APPROVED BY: Rio

UNIT: mm

Website: <http://www.bocentech.com>

DATE: 2011-9-24