




Interface	
1	GND
2	VDD
3	V0
4	RS
5	RW
6	E
7	DB0
8	DB1
9	DB2
10	DB3
11	DB4
12	DB5
13	DB6
14	DB7
15	PSB
16	N.C
17	RST
18	VOUT
19	LED-A(+5V)
20	LED-K



SPECIFICATIONS:

- | | |
|---------------------------|--------------------------------------|
| 1. DISPLAY TYPE: | STN / NEGATIVE (BLUE) / TRANSMISSIVE |
| 2. DRIVE IC: | AIP31107, AIP31108 |
| 3. CONNECTOR: | ZEBRA |
| 4. OPERATING VOLTAGE: | 5.0V |
| 5. OPERATING TEMPERATURE: | -20 ~ 70°C |
| 6. STORAGE TEMPERATURE: | -30 ~ 80°C |
| 7. DRIVE MODE: | 1/32 DUTY, 1/6 BIAS |
| 8. VIEWING ANGLE: | 6 O'CLOCK |
| 9. BACKLIGHT: | WHITE LED, I = 80mA, VBL = 3.0V |
| 10. CUSTOMER PART NO.: | BOCEN STANDARD PRODUCT |

BOCEN DISPLAY TECHNOLOGY CO., LTD.

DESIGNED BY: Mike	BB12864-10	VERSION: 1.0
CHECKED BY: William		NO.: 1 OF 1
APPROVED BY: Shawn		UNIT: mm
Website: http://www.bocentech.com		DATE: 2011-06-29