

**CN1**


PIN	SYMBOL
1	VSS
2	VDD
3	V0
4	A0
5	/WR(R/W)
6	/RD(E)
7~14	DB0~DB7
15	/CS
16	/RST
17	VEE
18	SEL1
19	LED-A
20	LED-K
21	NC
22	NC

**CN2**

PIN	SYMBOL
1	D0
2	D1
3	D2
4	D3
5	/DISPOFF
6	FLM
7	M
8	LP
9	CP
10	VDD
11	VSS
12	VEE
13	V0
14	FG
15	(NC) LED-A
16	(NC) LED-K

**SPECIFICATIONS:**

- |                           |  |
|---------------------------|--|
| 1. DISPLAY TYPE:          | FSTN / POSITIVE (GRAY) / TRANSFLECTIVE |
| 2. DRIVE IC:              | RA8835 or EQV.                         |
| 3. UNSPECIFIED TOLERANCE: | ±0.3 MM                                |
| 4. OPERATING VOLTAGE:     | VDD = 5.0V                             |
| 5. OPERATING TEMPERATURE: | -20 ~ 70°C                             |
| 6. STORAGE TEMPERATURE:   | -30 ~ 80°C                             |
| 7. DRIVE MODE:            | 1/240 DUTY, 1/16 BIAS                  |
| 8. VIEWING ANGLE:         | 6 O'CLOCK                              |
| 9. BACKLIGHT:             | WHITE LED, VF = 5.0V                   |
| 10. CUSTOMER PART NO.:    | BOCEN STANDARD PRODUCT                 |



**BOCEN DISPLAY TECHNOLOGY CO., LTD.**

DESIGNED BY: Shawn	<b>BB320240-09</b>	VERSION: 1.0
CHECKED BY: William		NO.: 1 OF 1
APPROVED BY: Rio		UNIT: mm
Website: <a href="http://www.bocentech.com">http://www.bocentech.com</a>		DATE: 2013-10-8