




PIN	SYMBOL
1	VDD(3.3V)
2	VSS
3	/CS
4	RS
5	/WR
6	/RD
7	DB0
8	DB1
9	DB2
10	DB3
11	DB4
12	DB5
13	DB6
14	DB7
15	/RST
16	BLA(3.3V)



SPECIFICATIONS:

- | | |
|---------------------------|-------------------------------|
| 1. DISPLAY TYPE: | STN / NAGATIVE / TRANSMISSIVE |
| 2. DRIVE IC: | ST7586S |
| 3. OPERATING VOLTAGE: | Vdd=3.3V;Vop=15V |
| 4. OPERATING TEMPERATURE: | -20°C ~ +70°C |
| 5. STORAGE TEMPERATURE: | -30°C ~+ 80°C |
| 6. DRIVE MODE: | 1/160 DUTY, 1/12 BIAS |
| 7. VIEWING ANGLE: | 6 O'CLOCK |
| 8. BACKLIGHT: | LED (WHITE, IF=100MA) |
| 9. CUSTOMER PART NO.: | BOCEN STANDARD PRODUCT |


BOCEN DISPLAY TECHNOLOGY CO., LTD.

DESIGNED BY: Shawn

BG240160-01

VERSION: 1.0

CHECKED BY: William



NO.: 1 OF 3

APPROVED BY: Rio

UNIT: mm

Website: <http://www.bocentech.com>

DATE: 2013-7-31