

COM & SEG LAYOUT

PIN	SYMBOL
1	ESD
2	RS
3	/WR
4	DB0
5	DB1
6	DB2
7	DB3
8	DB4
9	DB5
10	DB6
11	DB7
12	/RD
13	/RST
14	IF1
15	IF2
16	IF3
17	/CS
18	VDD1
19	VD1
20	VSS
21	VDD
22	VM
23	VO
24	XV0
25	VG
26	ESD

SPECIFICATIONS:

- | | |
|---------------------------|-------------------------------|
| 1. DISPLAY TYPE: | STN / NAGATIVE / TRANSMISSIVE |
| 2. DRIVE IC: | ST7586S |
| 3. OPERATING VOLTAGE: | Vdd=3.3V |
| 4. OPERATING TEMPERATURE: | -20°C ~ +70°C |
| 5. STORAGE TEMPERATURE: | -30°C ~+ 80°C |
| 6. DRIVE MODE: | 1/160 DUTY, 1/12 BIAS |
| 7. VIEWING ANGLE: | 6 O'CLOCK |
| 8. BACKLIGHT: | ----- |
| 9. CUSTOMER PART NO.: | BOCEN STANDARD PRODUCT |


BOCEN DISPLAY TECHNOLOGY CO., LTD.

DESIGNED BY: Shawn

BG240160-03

VERSION: 1.0

CHECKED BY: William



NO.: 1 OF 3

APPROVED BY: Rio

UNIT: mm

Website: <http://www.bocentech.com>

DATE: 2016-5-21