


SCALE:30:1





COM & SEG LAYOUT

PIN	SYMBOL
1	VSS
2	A0
3	WR
4	RD
5	XCS
6	RST
7	VDD(3.3V)
8	D0
9	D1
10	D2
11	D3
12	D4
13	D5
14	D6
15	D7
16	K
17	NC
18	A(5V)

SPECIFICATIONS:

- 1. DISPLAY TYPE: FSTN / B-W / POSITIVE / TRANSFLECTIVE
- 2. DRIVE IC: UC1698U
- 3. OPERATING VOLTAGE: Vdd=3.3V; Vop=16.5V
- 4. OPERATING TEMPERATURE: -30°C ~ +80°C
- 5. STORAGE TEMPERATURE: -30°C ~+ 80°C
- 6. DRIVE MODE: 1/160DUTY, 1/10 BIAS
- 7. VIEWING ANGLE: 6 O'CLOCK
- 8. BACKLIGHT: 5 PCS White LED; If<80mA; VF=5V
- 9. CUSTOMER PART NO.: BOCEN STANDARD PRODUCT

BOCEN DISPLAY TECHNOLOGY CO., LTD.

DESIGNED BY: Shawn	BG160160-02	VERSION: 1.0
CHECKED BY: William		NO.: 1 OF 3
APPROVED BY: Rio		UNIT: mm
Website: http://www.bocentech.com		DATE: 2013-01-14