


SCALE:30:1



COM & SEG LAYOUT

CN1	
PIN	SYMBOL
1	VSS
2	A0
3	WR
4	RD
5	XCS
6	RST
7	VDD
8	D0
9	D1
10	D2
11	D3
12	D4
13	D5
14	D6
15	D7
16	LED-K
17	NC
18	LED-A

CN2	
PIN	SYMBOL
1	KEY1
2	KEY2
3	KEY3
4	KEY4
5	KEY5
6	COMMON

SPECIFICATIONS:

- DISPLAY TYPE: FSTN / POSITIVE / TRANSFLECTIVE
- DRIVE IC: UC1698U
- OPERATING VOLTAGE: Vdd=3.3V; Vop=16.5V
- OPERATING TEMPERATURE: -20°C ~ +70°C
- STORAGE TEMPERATURE: -30°C ~+ 80°C
- DRIVE MODE: 1/160DUTY, 1/10 BIAS
- VIEWING ANGLE: 6 O'CLOCK
- BACKLIGHT: 4PCS White LED; If=60mA; VF=3.0V
- CUSTOMER PART NO.: BOCEN STANDARD PRODUCT

BOCEN DISPLAY TECHNOLOGY CO., LTD.

DESIGNED BY: Shawn	BG160160-04	VERSION: 1.0
CHECKED BY: William		NO.: 1 OF 3
APPROVED BY: Rio		UNIT: mm
Website: http://www.bocentech.com		DATE: 2017-05-23