



| PIN | SYMBOL |
|-----|---------|
| 1 | ESD |
| 2 | D15 |
| 3 | D13 |
| 4 | D8(SDA) |
| 5 | D7 |
| 6 | D6 |
| 7 | D5 |
| 8 | D4 |
| 9 | D3 |
| 10 | D2 |
| 11 | D1 |
| 12 | DO(SCK) |
| 13 | RST |
| 14 | WR0 |
| 15 | WR1 |
| 16 | CD |
| 17 | CS0 |
| 18 | BM0 |
| 19 | TST4 |
| 20 | VSS |
| 21 | VDD |
| 22 | VB0+ |
| 23 | VB1+ |
| 24 | VB1- |
| 25 | VB0- |
| 26 | VS- |
| 27 | VS+ |
| 28 | VIN |
| 29 | VOUT |
| 30 | ESD |

SPECIFICATIONS:

1. DISPLAY TYPE: FSTN / POSITIVE / TRANSFLECTIVE
2. DRIVE IC: UC1698U
3. OPERATING VOLTAGE: Vdd=3.3V; Vop=16.3V
4. OPERATING TEMPERATURE: -20°C ~ +70°C
5. STORAGE TEMPERATURE: -30°C ~+ 80°C
6. DRIVE MODE: 1/160DUTY, 1/10 BIAS
7. VIEWING ANGLE: 6 O'CLOCK
8. BACKLIGHT: White LED; If=90mA; VF=3.0V
9. CUSTOMER PART NO.: BOCEN STANDARD PRODUCT

BOCEN DISPLAY TECHNOLOGY CO., LTD.

| | | |
|--|---|------------------|
| DESIGNED BY: Shawn | BG160160-05 | VERSION: 1.0 |
| CHECKED BY: William |  | NO.: 1 OF 3 |
| APPROVED BY: Rio |  | UNIT: mm |
| Website: http://www.bocentech.com | | DATE: 2017-09-16 |