

PIN	SYMBOL	PIN	SYMBOL
1	A0	21	IF3
2	RW_WR	22	XCS
3	D0	23	VDD
4	D1	24	VSS
5	D2	25	VDD
6	D3	26	C7P
7	D4	27	C5P
8	D5	28	C3P
9	D6	29	C1N
10	D7	30	C1P
11	D8	31	C2P
12	D9	32	C2N
13	D10	33	C4P
14	D11	34	C6P
15	D12	35	VLCD
16	D13	36	V4
17	D14	37	V3
18	D15	38	V2
19	E_RD	39	V1
20	RST	40	V0

SPECIFICATIONS:

- 1. DISPLAY TYPE: FSTN / POSITIVE / TRANSFLECTIVE
- 2. DRIVE IC: ST7529
- 3. OPERATING VOLTAGE: Vdd=3.3V; Vop=16V
- 4. OPERATING TEMPERATURE: 0°C ~ +50°C
- 5. STORAGE TEMPERATURE: -20°C ~+70°C
- 6. DRIVE MODE: 1/160DUTY, 1/10 BIAS
- 7. VIEWING ANGLE: 6 O'CLOCK
- 8. BACKLIGHT: NO
- 9. CUSTOMER PART NO.: BOCEN STANDARD PRODUCT


BOCEN DISPLAY TECHNOLOGY CO., LTD.

DESIGNED BY: Shawn

BG160160-07

VERSION: 1.0

CHECKED BY: William



NO.: 1 OF 3

APPROVED BY: Rio

UNIT: mm

Website: <http://www.bocentech.com>

DATE: 2016-10-20