




INTERFACE		
1	SCK	○ P1.0
2	SDA	○ P1.1
3	/RES	○ P3.6
4	/CS0	○ P3.5
5	CD	○ P3.7
6	VSS	○ GND
7	VDD	○ +3.3V
8	VB0+	2.2uF
9	VB1+	2.2uF
10	VB1-	
11	VB0-	
12	VLCD	330nF
13	BLK	3.3M ohm
14	BLA	△ GND



SPECIFICATIONS:

- | | |
|---------------------------|---|
| 1. DISPLAY TYPE: | FSTN / POSITIVE (GREY) / TRANSMISSIVE |
| 2. DRIVE IC: | UC1617S or EQV. |
| 3. CONNECTOR: | FPC |
| 4. OPERATING VOLTAGE: | VOP = 13.0 V, VDD = 3.0V |
| 5. OPERATING TEMPERATURE: | 0 ~ 50°C |
| 6. STORAGE TEMPERATURE: | -10 ~ 60°C |
| 7. DRIVE MODE: | 1/128 DUTY, 1/12 BIAS |
| 8. VIEWING ANGLE: | 6 O'CLOCK |
| 9. BACKLIGHT: | WHITE LED 5 PCS, Vf=3.0±0.20, If = 75mA |
| 10. CUSTOMER PART NO.: | BOCEN STANDERD PRODUCT |

BOCEN DISPLAY TECHNOLOGY CO., LTD.

DESIGNED BY: Shawn	BG128128-17	VERSION: 1.0
CHECKED BY: William		NO.: 1 OF 1
APPROVED BY: Rio		UNIT: mm
Website: http://www.bocentech.com		DATE: 2019-8-26