




PIN	SYMBOL
1	VG
2	XV0
3	V0
4	VM
5	VDD
6	VSS
7	VD1
8	VDD1
9	CSB
10	RSTB
11	D1
12	D0
13	A0
14	ESD



SPECIFICATIONS:

- | | |
|---------------------------|----------------------------------|
| 1. DISPLAY TYPE: | FSTN / POSITIVE / TRANSFLECTIVE |
| 2. DRIVE IC: | ST7586S |
| 3. OPERATING VOLTAGE: | Vop=12V; Vdd=3V |
| 4. OPERATING TEMPERATURE: | -10°C ~ +60°C |
| 5. STORAGE TEMPERATURE: | -20°C ~ +70°C |
| 6. DRIVE MODE: | 1/64DUTY, 1/9BIAS |
| 7. VIEWING ANGLE: | 6 O'CLOCK |
| 8. BACKLIGHT: | 4PCS White LED, VF=3.0V; IF<80mA |
| 9. CUSTOMER PART NO.: | BOCEN STANDARD PRODUCT |

BOCEN DISPLAY TECHNOLOGY CO., LTD.

DESIGNED BY: Shawn	BG28064-01	VERSION: 1.0
CHECKED BY: William		NO.: 1 OF 3
APPROVED BY: Rio		UNIT: mm
Website: http://www.bocentech.com		DATE: 2017-11-07