



| PIN | SYMBOL |
|-----|--------|
| 1 | SDA |
| 2 | SCLK |
| 3 | /RESET |
| 4 | A0 |
| 5 | /CSB |
| 6 | VSS |
| 7 | VDD |
| 8 | C1- |
| 9 | C1+ |
| 10 | XV0 |
| 11 | V0 |
| 12 | VG |

SPECIFICATIONS:

- 1. DISPLAY TYPE: FSTN / POSITIVE / TRANSFLECTIVE
- 2. DRIVE IC: ST75256
- 3. OPERATING VOLTAGE: Vop=9V; Vdd=3V
- 4. OPERATING TEMPERATURE: -20°C ~ +70°C
- 5. STORAGE TEMPERATURE: -30°C ~+80°C
- 6. DRIVE MODE: 1/32DUTY, 1/9BIAS
- 7. VIEWING ANGLE: 6 O'CLOCK
- 8. BACKLIGHT: 10PCS GREEN LED,VF=3.0V; IF=120mA
- 9. CUSTOMER PART NO.: BOCEN STANDARD PRODUCT

BOCEN DISPLAY TECHNOLOGY CO., LTD.

| | | |
|--------------------------------------------------------------------------|-------------------|------------------|
| DESIGNED BY: Shawn | BG25632-03 | VERSION: 1.0 |
| CHECKED BY: William | | NO.: 1 OF 3 |
| APPROVED BY: Rio | | UNIT: mm |
| Website: http://www.bocentech.com | | DATE: 2018-05-04 |