






PIN	SYMBOL
1	VG
2	XV0
3	V0
4	VDD
5	VSS
6	CS0
7	A0
8	RST
9	SCL
10	SDA

SPECIFICATIONS:

- | | |
|---------------------------|----------------------------------|
| 1. DISPLAY TYPE: | DFSTN / NEGATIVE/ TRANSMISSIVE |
| 2. DRIVE IC: | ST7525 |
| 3. OPERATING VOLTAGE: | Vlcd=8.5V; Vdd=3.3V |
| 4. OPERATING TEMPERATURE: | -20°C ~ +70°C |
| 5. STORAGE TEMPERATURE: | -30°C ~+80°C |
| 6. DRIVE MODE: | 1/49DUTY, 1/8BIAS |
| 7. VIEWING ANGLE: | 6 O'CLOCK |
| 8. BACKLIGHT: | 2PCS white LED; IF=30mA; VF=3.3V |
| 9. CUSTOMER PART NO.: | BOCEN STANDARD PRODUCT |



BOCEN DISPLAY TECHNOLOGY CO., LTD.

DESIGNED BY: Shawn	BG19248-01	VERSION: 1.0
CHECKED BY: William		NO.: 1 OF 3
APPROVED BY: Rio		UNIT: mm
Website: http://www.bocentech.com		DATE: 2019-04-13