



LCD LAYOUT



BACKLIGHT CIRCUIT
2PCS WHITE LEDS

PIN	SYMBOL
1	GND
2	LED-K
3	LED-A
4	CS0
5	RSTB
6	CD
7	WR0
8	WR1
9	D0
10	D1
11	D2
12	D3
13	D4
14	D5
15	D6
16	D7
17	BM0
18	BM1
19	POR
20	VDD
21	VSS
22	TST4
23	VB0-
24	VB0+
25	VB1-
26	VB1+
27	VLCD
28	GND

SPECIFICATIONS:

- | | |
|---------------------------|-----------------------------------|
| 1. DISPLAY TYPE: | FSTN / POSITIVE/ TRANSFLECTIVE |
| 2. DRIVE IC: | UC1604C |
| 3. OPERATING VOLTAGE: | Vop=10V; Vdd=3.3V |
| 4. OPERATING TEMPERATURE: | -20°C ~ +70°C |
| 5. STORAGE TEMPERATURE: | -30°C ~+80°C |
| 6. DRIVE MODE: | 1/64DUTY, 1/9BIAS |
| 7. VIEWING ANGLE: | 6 O'CLOCK |
| 8. BACKLIGHT: | 2PCS WHITE LEDS, IF=40mA, VF=3.0V |
| 9. CUSTOMER PART NO.: | BOCEN STANDARD PRODUCT |


BOCEN DISPLAY TECHNOLOGY CO., LTD.

DESIGNED BY: Shawn

BG16048-05

VERSION: 1.0

CHECKED BY: William



NO.: 1 OF 3

APPROVED BY: Rio

UNIT: mm

Website: <http://www.bocentech.com>

DATE: 2018-05-22