

PIN	SYMBOL
1	VBL
2	VBL
3	VCC
4	VCC
5	GND
6	GND
7	DATA
8	GND
9	CLK
10	LCLK

SPECIFICATIONS:

- | | |
|---------------------------|------------------------------|
| 1. DISPLAY TYPE: | TN / POSITIVE / TRANSMISSIVE |
| 2. DRIVE IC: | NT7063 or EQV. |
| 3. CONNECTOR: | PIN |
| 4. OPERATING VOLTAGE: | 4.5~5.2V |
| 5. OPERATING TEMPERATURE: | -30 ~ 80°C |
| 6. STORAGE TEMPERATURE: | -40 ~ 90°C |
| 7. DRIVE MODE: | 1/1 DUTY, 1/1 BIAS |
| 8. VIEWING ANGLE: | 6 O'CLOCK |
| 9. CUSTOMER PART NO.: | BOCEN STANDARD PRODUCT |


BOCEN DISPLAY TECHNOLOGY CO., LTD.

DESIGNED BY: Shawn

BB1001-01

VERSION: 1.0

CHECKED BY: William



NO.: 1 OF 1

APPROVED BY: Rio

UNIT: mm

Website: <http://www.bocentech.com>

DATE: 2018-5-3