


PIN	SYMBOL
1	LEDA
2	LEDK
3	LEDK
4	GND
5	VCI
6	RESET
7	NC
8	NC
9	SDA
10	SCK
11	CS
12	PCLK
13	DE
14	VSYNC
15	HSYNC
16	DB0
17	DB1
18	DB2
19	DB3
20	DB4
21	DB5
22	DB6
23	DB7
24	DB8
25	DB9
26	DB10
27	DB11
28	DB12
29	DB13
30	DB14
31	DB15
32	DB16
33	DB17
34	GND
35	TP-INT
36	TP-SDA
37	TP-SCL
38	TP-RESET
39	TP-VCI
40	GND

1	TP-INT
2	TP-SDA
3	TP-SCL
4	TP-RESET
5	TP-VCI
6	GND

SPECIFICATIONS:

- 1. DISPLAY TYPE: 4.0" TFT / IPS / 480*480
- 2. DRIVE IC: ST7701S
- 3. OPERATING TEMPERATURE: -20 ~ 70°C
- 4. STORAGE TEMPERATURE: -30 ~ 80°C
- 5. BACKLIGHT: 8 WHITE LED, If = 40mA
- 6. CUSTOMER PART NO.: BOCEN STANDARD PRODUCT

BACKLIGHT LED CIRCUIT DIAGRAM



BOCEN DISPLAY TECHNOLOGY CO., LTD.

DESIGNED BY: David	BF4040-06	VERSION: 1.0
CHECKED BY: William		NO.: 1 OF 1
APPROVED BY: Rio		UNIT: mm
Website: http://www.bocentech.com		DATE: 2022-07-22