


PIN	SYMBOL
1	VBL-
2	VBL+
3	GND
4	VDD
5	R0
6	R1
7	R2
8	R3
9	R4
10	R5
11	R6
12	R7
13	G0
14	G1
15	G2
16	G3
17	G4
18	G5
19	G6
20	G7
21	B0
22	B1
23	B2
24	B3
25	B4
26	B5
27	B6
28	B7
29	GND
30	DCLK
31	DISP
32	HSYNC
33	VSYNC
34	DE
35	NC
36	GND
37	NC/XR
38	NC/YD
39	NC/XL
40	NC/YU

SPECIFICATIONS:

- | | |
|---------------------------|------------------------|
| 1. DISPLAY TYPE: | 4.3"/ IPS / 480*272 |
| 2. DRIVE IC: | NV3047 |
| 3. OPERATING TEMPERATURE: | -20 ~ 70°C |
| 4. STORAGE TEMPERATURE: | -30 ~ 80°C |
| 5. VIEWING ANGLE: | ALL |
| 6. BACKLIGHT: | 12 WHITE LED, 60mA |
| 7. BRIGHTNESS: | 1000 CD/M ² |
| 8. CUSTOMER PART NO.: | BOCEN STANDARD PRODUCT |

BACKLIGHT CIRCUIT DIAGRAM



背光驱动 Vf = 23.2-24.8V; If = 60mA 双芯灯


BOCEN DISPLAY TECHNOLOGY CO., LTD.

DESIGNED BY: David

BF4340-10

VERSION: 1.0

CHECKED BY: William



NO.: 1 OF 1

APPROVED BY: Rio

UNIT: mm

Website: <http://www.bocentech.com>

DATE: 2021-12-30