



SCALE: 10:1



CIRCUIT DIAGRAM led 1*8=8





LCD LAYOUT

PIN	SYMBOL
1	VSS
2	VDD
3	VLCD
4	CD(A0)
5	WR(WR0)
6	RD(WR1)
7	D0
8	D1
9	D2
10	D3
11	D4
12	D5
13	D6
14	D7
15	RES
16	CS0
17	NC
18	NC
19	A
20	K

SPECIFICATIONS:

- | | |
|---------------------------|----------------------------------|
| 1. DISPLAY TYPE: | FSTN / POSITIVE / TRANSFLECTIVE |
| 2. DRIVE IC: | UC1701X |
| 3. OPERATING VOLTAGE: | Vop=8.5V; Vdd=3.3V |
| 4. OPERATING TEMPERATURE: | -20°C ~ +70°C |
| 5. STORAGE TEMPERATURE: | -30°C ~+80°C |
| 6. DRIVE MODE: | 1/68DUTY, 1/9BIAS |
| 7. BACKLIGHT: | 8PCS Y-G LEDS, IF=120mA, VF=2.0V |
| 8. VIEWING ANGLE: | 6 O'CLOCK |
| 9. CUSTOMER PART NO.: | BOCEN STANDARD PRODUCT |

BOCEN DISPLAY TECHNOLOGY CO., LTD.

DESIGNED BY: Shawn	BG9732-01	VERSION: 1.0
CHECKED BY: William		NO.: 1 OF 1
APPROVED BY: Rio		UNIT: mm
Website: http://www.bocentech.com		DATE: 2016-09-29