


PIN	SYMBOL
1	A
2	K
3	CS0
4	RST
5	CD
6	SCK
7	SDA
8	VDD
9	VSS
10	VB0+
11	VB0-
12	VB1-
13	VB1+
14	VLCD



LCD LAYOUT

**SPECIFICATIONS:**

- |                           |                                   |
|---------------------------|-----------------------------------|
| 1. DISPLAY TYPE:          | FSTN / POSITIVE / TRANSFLECTIVE   |
| 2. DRIVE IC:              | UC1705                            |
| 3. OPERATING VOLTAGE:     | Vop=9.10V; Vdd=3.3V               |
| 4. OPERATING TEMPERATURE: | 0°C ~ +50°C                       |
| 5. STORAGE TEMPERATURE:   | -20°C ~+70°C                      |
| 6. DRIVE MODE:            | 1/33DUTY, 1/6BIAS                 |
| 7. BACKLIGHT:             | 2PCS WHITE LED, IF=30mA, VF=3.10V |
| 8. VIEWING ANGLE:         | 12 O'CLOCK                        |
| 9. CUSTOMER PART NO.:     | BOCEN STANDARD PRODUCT            |

**BOCEN DISPLAY TECHNOLOGY CO., LTD.**

DESIGNED BY: Shawn	<b>BG12832-02</b>	VERSION: 1.0
CHECKED BY: William		NO.: 1 OF 1
APPROVED BY: Rio		UNIT: mm
Website: <a href="http://www.bocentech.com">http://www.bocentech.com</a>		DATE: 2015-05-04