

PIN	SYMBOL
1	VDD
2	C86
3	VSS
4	V0
5	V1
6	V2
7	V3
8	V4
9	CAP2N
10	CAP2P
11	CAP1P
12	CAP1N
13	CAP3P
14	VOUT
15	VSS
16	D7
17	D6
18	D5
19	D4
20	D3
21	D2
22	D1
23	D0
24	RD/(E)
25	WR(R/W)
26	A0
27	/RES
28	/CS1

### SPECIFICATIONS:

- |                           |                                |
|---------------------------|--------------------------------|
| 1. DISPLAY TYPE:          | FSTN / POSITIVE / TRANSMISSIVE |
| 2. DRIVE IC:              | ST7565R                        |
| 3. OPERATING VOLTAGE:     | Vop=6.0V; Vdd=3.0V             |
| 4. OPERATING TEMPERATURE: | -10°C ~ +60°C                  |
| 5. STORAGE TEMPERATURE:   | -30°C ~ +80°C                  |
| 6. DRIVE MODE:            | 1/33DUTY, 1/6BIAS              |
| 7. BACKLIGHT:             | -----                          |
| 8. VIEWING ANGLE:         | 120'CLOCK                      |
| 9. CUSTOMER PART NO.:     | BOCEN STANDARD PRODUCT         |


## BOCEN DISPLAY TECHNOLOGY CO., LTD.

DESIGNED BY: Shawn

**BG12832-05**

VERSION: 1.0

CHECKED BY: William



NO.: 1 OF 3

APPROVED BY: Rio

UNIT: mm

Website: <http://www.bocentech.com>

DATE: 2015-07-04