



PIN	SYMBOL	PIN	SYMBOL
1	VDD	15	VSS
2	NC	16	SDA
3	NC	17	SCL
4	VG	18	NC
5	NC	19	NC
6	NC	20	NC
7	NC	21	NC
8	NC	22	NC
9	XV0	23	NC
10	VO	24	LED+
11	NC	25	LED-
12	NC	26	A0
13	NC	27	/RES
14	NC	28	/CS



DOT DETAIL SCALE: 20:1



LCD LAYOUT

**SPECIFICATIONS:**

- 1. DISPLAY TYPE: FSTN / POSITIVE / TRANSFLECTIVE
- 2. DRIVE IC: ST7567
- 3. OPERATING VOLTAGE: Vop=7.5V; Vdd=3.0V
- 4. OPERATING TEMPERATURE: -20°C ~ +70°C
- 5. STORAGE TEMPERATURE: -30°C ~+80°C
- 6. DRIVE MODE: 1/33DUTY, 1/6BIAS
- 7. BACKLIGHT: 2PCS WHITE LED, IF=30mA, VF=3.0V
- 8. VIEWING ANGLE: 12 O'CLOCK
- 9. CUSTOMER PART NO.: BOCEN STANDARD PRODUCT

**BOCEN DISPLAY TECHNOLOGY CO., LTD.**

DESIGNED BY: Shawn	<b>BG12832-11</b>	VERSION: 1.0
CHECKED BY: William		NO.: 1 OF 3
APPROVED BY: Rio		UNIT: mm
Website: <a href="http://www.bocentech.com">http://www.bocentech.com</a>		DATE: 2016-08-03