



PIN	SYMBOL
1	CSB
2	RSTB
3	A0
4	SCL
5	SDA
6	VDD
7	VSS
8	NC
9	NC
10	V0
11	XV0
12	NC
13	NC
14	NC
15	NC
16	NC
17	NC
18	VG
19	LEDA
20	LEDK

**SPECIFICATIONS:**

- |                           |                                    |
|---------------------------|------------------------------------|
| 1. DISPLAY TYPE:          | STN / Y-G / POSITIVE/ TRANFLECTIVE |
| 2. DRIVE IC:              | ST7567                             |
| 3. OPERATING VOLTAGE:     | Vop=8.0V; Vdd=3.0V                 |
| 4. OPERATING TEMPERATURE: | -20°C ~ +70°C                      |
| 5. STORAGE TEMPERATURE:   | -30°C ~+80°C                       |
| 6. DRIVE MODE:            | 1/49DUTY, 1/8BIAS                  |
| 7. VIEWING ANGLE:         | 6 O'CLOCK                          |
| 8. BACKLIGHT:             | 2PCS WHITE LED, IF=30mA; VF=3.0V   |
| 9. CUSTOMER PART NO.:     | BOCEN STANDARD PRODUCT             |

<b>BOCEN DISPLAY TECHNOLOGY CO., LTD.</b>		
DESIGNED BY: Shawn	<b>BG12848-07</b>	VERSION: 1.0
CHECKED BY: William		NO.: 1 OF 1
APPROVED BY: Rio		UNIT: mm
Website: <a href="http://www.bocentech.com">http://www.bocentech.com</a>		DATE: 2018-06-13