



PIN	SYMBOL
1	CSB
2	/RES
3	CD
4	D6(SCL)
5	D7(SDA)
6	VDD
7	VSS
8	VB0+
9	VB0-
10	VB1-
11	VB1+
12	VLCD



COM & SEG LAYOUT

SPECIFICATIONS:

- 1. DISPLAY TYPE: FSTN / POSITIVE/ REFLECTIVE
- 2. DRIVE IC: UC1701XGAA
- 3. OPERATING VOLTAGE: Vop=8.5V; Vdd=3.3V
- 4. OPERATING TEMPERATURE: 0°C ~ +50°C
- 5. STORAGE TEMPERATURE: -10°C ~+60°C
- 6. DRIVE MODE: 1/49DUTY, 1/8BIAS
- 7. VIEWING ANGLE: 6 O'CLOCK
- 8. BACKLIGHT: -----
- 9. CUSTOMER PART NO.: BOCEN STANDARD PRODUCT

BOCEN DISPLAY TECHNOLOGY CO., LTD.

DESIGNED BY: Shawn	BG12848-13	VERSION: 1.0
CHECKED BY: William		NO.: 1 OF 1
APPROVED BY: Rio		UNIT: mm
Website: http://www.bocentech.com		DATE: 2016-04-19