

PIN	SYMBOL
1	CSB
2	RSTB
3	A0
4	SCL
5	SDA
6	VDD
7	VSS
8	V0
9	XV0
10	VG
11	NC
12	LEDA
13	NC
14	LEDK

**SPECIFICATIONS:**

- 1. DISPLAY TYPE: STN / Y-G / POSITIVE / TRANSFLECTIVE
- 2. DRIVE IC: ST7567
- 3. OPERATING VOLTAGE: V<sub>lcd</sub>=8.0V; V<sub>dd</sub>=3.0V
- 4. OPERATING TEMPERATURE: -20°C ~ +70°C
- 5. STORAGE TEMPERATURE: -30°C ~ +80°C
- 6. DRIVE MODE: 1/49DUTY, 1/8BIAS
- 7. VIEWING ANGLE: 6 O'CLOCK
- 8. BACKLIGHT: 2PCS WHITE, I<sub>F</sub>=30mA, V<sub>F</sub>=3.0V
- 9. CUSTOMER PART NO.: BOCEN STANDARD PRODUCT


**BOCEN DISPLAY TECHNOLOGY CO., LTD.**

DESIGNED BY: Shawn

**BG12848-16**

VERSION: 1.0

CHECKED BY: William



NO.: 1 OF 1

APPROVED BY: Rio

UNIT: mm

Website: <http://www.bocentech.com>

DATE: 2019-11-05