




PIN	SYMBOL
1	XRESET
2	DB6
3	DB7
4	VSS
5	DIRC
6	SHL
7	VDD
8	VIN
9	VOUT
10	CAP1P
11	CAP1N
12	N.C

### SPECIFICATIONS:

- |                           |                                |
|---------------------------|--------------------------------|
| 1. DISPLAY TYPE:          | FFSTN / NEGATIVE/ TRANSMISSIVE |
| 2. DRIVE IC:              | SPLC792A-002A                  |
| 3. OPERATING VOLTAGE:     | Vop=5.6V; Vdd=3.3V             |
| 4. OPERATING TEMPERATURE: | -10°C ~ +60°C                  |
| 5. STORAGE TEMPERATURE:   | -20°C ~ +70°C                  |
| 6. DRIVE MODE:            | 1/17 DUTY, 1/5 BIAS            |
| 7. VIEWING ANGLE:         | 9 O'CLOCK                      |
| 8. BACKLIGHT:             | White LED, IF=30mA; VF=3.0V    |
| 9. CUSTOMER PART NO.:     | BOCEN STANDARD PRODUCT         |




## BOCEN DISPLAY TECHNOLOGY CO., LTD.

DESIGNED BY: Shawn

**BG1602-18**

VERSION: 1.0

CHECKED BY: William



NO.: 1 OF 3

APPROVED BY: Rio

UNIT: mm

Website: <http://www.bocentech.com>

DATE: 2019-04-30