



PIN	SYMBOL
1	VSS
2	LED+
3	LED-
4	BM1
5	BM0
6	CS
7	RESET
8	CD
9	WR
10	RD
11	DB0
12	DB1
13	DB2
14	DB3
15	DB4
16	DB5
17	DB6
18	DB7
19	VDD
20	VSS

SPECIFICATIONS:

- 1. DISPLAY TYPE: FSTN / B&W / POSITIVE / TRANSFLECTIVE
- 2. DRIVE IC: UC1608X
- 3. OPERATING VOLTAGE: Vdd=3.0V; Vlcd=13.6V
- 4. OPERATING TEMPERATURE: -30°C ~ +80°C
- 5. STORAGE TEMPERATURE: -40°C ~+ 85°C
- 6. DRIVE MODE: 1/128 DUTY, 1/12 BIAS
- 7. VIEWING ANGLE: 6 O'CLOCK
- 8. BACKLIGHT: White, 16.8~19.2V; If=10mA
- 9. CUSTOMER PART NO.: BOCEN STANDARD PRODUCT

BOCEN DISPLAY TECHNOLOGY CO., LTD.		
DESIGNED BY: Shawn	BG240128-05	VERSION: 1.0
CHECKED BY: William		NO.: 1 OF 1
APPROVED BY: Rio		UNIT: mm
Website: http://www.bocentech.com		DATE: 2019-5-9