



DOT SIZE:

PIN	SYMBOL
1	VSS
2	VDD(5V)
3	V0
4	RS
5	RW
6	E
7	DB0
8	DB1
9	DB2
10	DB3
11	DB4
12	DB5
13	DB6
14	DB7
15	LED-A(5.0V)
16	LED-K

SPECIFICATIONS:

- | | |
|---------------------------|---------------------------------------|
| 1. DISPLAY TYPE: | STN (Y/G) / POSITIVE/ TRANSFLECTIVE |
| 2. DRIVE IC: | ST7066U-0T or EQV. |
| 3. OPERATING VOLTAGE: | VOP = 5.0 V, VDD = 5.0V |
| 4. OPERATING TEMPERATURE: | -20 ~ 70°C |
| 5. STORAGE TEMPERATURE: | -30 ~ 80°C |
| 6. DRIVE MODE: | 1/16 DUTY, 1/5 BIAS |
| 7. VIEWING ANGLE: | 6 O'CLOCK |
| 8. BACKLIGHT: | Yellow-Green LED, I = 40mA |
| 9. CUSTOMER PART NO.: | BOCEN STANDARD PRODUCT |

BOCEN DISPLAY TECHNOLOGY CO., LTD.

DESIGNED BY: Sylar	BB1604-03	VERSION: 1.0
CHECKED BY: William	 	NO.: 1 OF 1
APPROVED BY: Rio		UNIT: mm
Website: http://www.bocentech.com		DATE: 2012-10-30