



PIN	SYMBOL
1	GND
2	AVDD
3	VCC
4	R0
5	R1
6	R2
7	R3
8	R4
9	R5
10	R6
11	R7
12	G0
13	G1
14	G2
15	G3
16	G4
17	G5
18	G6
19	G7
20	B0
21	B1
22	B2
23	B3
24	B4
25	B5
26	B6
27	B7
28	DCLK
29	DE
30	HSYNC
31	VSYNC
32	MODE
33	NC
34	NC
35	NC
36	VCC
37	NC
38	GND
39	GND
40	AVDD
41	VCOM
42	DITH
43	NC
44	NC
45	NC
46	NC
47	NC
48	NC
49	NC
50	NC
51	NC
52	NC
53	NC
54	NC
55	NC
56	VGH
57	VCC
58	VGL
59	GND
60	NC

SPECIFICATIONS:

- 1. DISPLAY TYPE: 10.4"/ TN / 800*600
- 2. DRIVE IC: HX8282-A02 & HX8696-A
- 3. OPERATING TEMPERATURE: -20 ~ 70°C
- 4. STORAGE TEMPERATURE: -30 ~ 80°C
- 5. VIEWING ANGLE: 12 O'CLOCK
- 6. BACKLIGHT: 12parallel*3series WHITE LED, Vf=9.6v,If=240mA
- 7. BRIGHTNESS: 350 CD/M²
- 8. CUSTOMER PART NO.: BOCEN STANDARD PRODUCT

BOCEN DISPLAY TECHNOLOGY CO., LTD.

DESIGNED BY: David	BF10460-01	VERSION: 1.0
CHECKED BY: William		NO.: 1 OF 1
APPROVED BY: Rio		UNIT: mm
Website: http://www.bocentech.com		DATE: 2023-09-21