



逻辑:



BACKLIGHT CIRCUIT (4并联电路):



PIN	SYMBOL
1	YD
2	XL
3	YU
4	XR
5	IDVDD
6	DB15
7	DB14
8	DB13
9	DB12
10	DB11
11	DB10
12	DB9
13	DB8
14	DB7
15	DB6
16	DB5
17	DB4
18	DB3
19	DB2
20	DB1
21	DB0
22	SDA(SDI)
23	DOTCLK
24	DE
25	HSYNC
26	VSYNC
27	RD
28	WR(DC)
29	DC(SCL)
30	CS
31	REAET
32	IM0
33	IM1
34	IM2
35	IM3
36	GND
37	VCI
38	NC
39	LEDA
40	LEDK

SPECIFICATIONS:

- DISPLAY TYPE: 2.4"/ IPS / 240*320
- DRIVE IC: ILI9341V
- OPERATING TEMPERATURE: -20 ~ 70°C
- STORAGE TEMPERATURE: -30 ~ 80°C
- VIEWING ANGLE: ALL
- BACKLIGHT: 4 WHITE LED, IF=3.2V,VF=4*20mA
- BRIGHTNESS: --
- CUSTOMER PART NO.: BOCEN STANDARD PRODUCT


BOCEN DISPLAY TECHNOLOGY CO., LTD.

DESIGNED BY: Sylar

BF2440-04R

VERSION: 1.0

CHECKED BY: William



NO.: 1 OF 1

APPROVED BY: Rio

UNIT: mm

Website: <http://www.bocentech.com>

DATE: 2023-11-13