

INTERFACE	
1	VSS
2	VDD(5.0V)
3	V0
4	RS
5	RW
6	E
7	DB0
8	DB1
9	DB2
10	DB3
11	DB4
12	DB5
13	DB6
14	DB7
15	LED-A(5.0V)
16	LED-K

SPECIFICATIONS:

- DISPLAY TYPE: STN / NEGATIVE (BLUE) / TRANSMISSITIVE
- DRIVE IC: AIP31066 or EQV.
- CONNECTOR: ZEBRA
- OPERATING VOLTAGE: VOP = 4.2 V, VDD = 5.0V
- OPERATING TEMPERATURE: -20 ~ 70°C
- STORAGE TEMPERATURE: -30 ~ 80°C
- DRIVE MODE: 1/16 DUTY, 1/5 BIAS
- VIEWING ANGLE: 6 O'CLOCK
- BACKLIGHT: WHITE LED, I = 15mA
- CUSTOMER PART NO.: BOCEN STANDARD PRODUCT


BOCEN DISPLAY TECHNOLOGY CO., LTD.

DESIGNED BY: Sylar

BB1602-10

VERSION: 1.0

CHECKED BY: William



NO.: 1 OF 1

APPROVED BY: Rio

UNIT: mm

Website: <http://www.bocentech.com>

DATE: 2023-11-15