



DOT SIZE

INTERFACE	
1	VDD(5V)
2	VSS
3	V0
4	DB0
5	DB1
6	DB2
7	DB3
8	DB4
9	DB5
10	DB6
11	DB7
12	/CS1
13	/CS2
14	/RST
15	R/W
16	D/I
17	E
18	VEE
19	LED-A(5V)
20	LED-K

**SPECIFICATIONS:**

- 1. DISPLAY TYPE: STN / NEGATIVE (BLUE) / TRANSMISSIVE
- 2. DRIVE IC: AIP31107/31108 or EQV.
- 3. CONNECTOR: ZEBRA
- 4. OPERATING VOLTAGE: VOP = 9.0 V, VDD = 5.0V
- 5. OPERATING TEMPERATURE: -20 ~ 70°C
- 6. STORAGE TEMPERATURE: -30 ~ 80°C
- 7. DRIVE MODE: 1/64 DUTY, 1/9 BIAS
- 8. VIEWING ANGLE: 6 O'CLOCK
- 9. BACKLIGHT: WHITE LED,
- 10. CUSTOMER PART NO.: BOCEN STANDARD PRODUCT

**BOCEN DISPLAY TECHNOLOGY CO., LTD.**

DESIGNED BY: Sylar	<b>BB12864-02</b>	VERSION: 1.0
CHECKED BY: William		NO.: 1 OF 1
APPROVED BY: Rio		UNIT: mm
Website: <a href="http://www.bocentech.com">http://www.bocentech.com</a>		DATE: 2017-02-23