

| PIN | NAME |
|-----|------|
| 1 | RST |
| 2 | RS |
| 3 | CSB |
| 4 | SCL |
| 5 | SI |
| 6 | VSS |
| 7 | VDD |
| 8 | VOUT |
| 9 | C1+ |
| 10 | C1- |

Specifications:

1. Display Mode: STN(BLUE)/Transmissive/Negative.
2. Viewing Angle: 6 0'clock.
3. Drive Method: 1/16 Duty, 1/5 Bias, Vop=5.5V, Vdd=3.0V.
4. OPERATING TEMPERATURE: -20°C~+70°C
5. STORAGE TEMPERATURE: -30°C~+80°C.
6. Connector: COG+FPC.
7. Drive IC: ST7032, 4-Line Serial
8. BACKLIGHT: 2PCS WHITE LEDS, IF=30mA & VF=2.8-3.0
9. CUSTOMER PART NO.: BOCEN STANDARD PRODUCT


BOCEN DISPLAY TECHNOLOGY CO., LTD.

DESIGNED BY: Sylar

BG1602-26

VERSION: 1.0

CHECKED BY: William



NO.: 1 OF 1

APPROVED BY: Rio

UNIT: mm

Website: <http://www.bocentech.com>

DATE: 2016-7-5