




PIN	SYMBOL
1	VSS
2	VDD
3	V0
4	RS
5	R/W
6	E
7	DB0
8	DB1
9	DB2
10	DB3
11	DB4
12	DB5
13	DB6
14	DB7
15	BL+
16	BL-



**SPECIFICATIONS:**

- |                           |                                 |
|---------------------------|---------------------------------|
| 1. DISPLAY TYPE:          | FSTN / POSITIVE / TRANSFLECTIVE |
| 2. DRIVE IC:              | ST7525                          |
| 3. OPERATING VOLTAGE:     | Vdd=5.0V                        |
| 4. OPERATING TEMPERATURE: | -20°C ~ +70°C                   |
| 5. STORAGE TEMPERATURE:   | -30°C ~+80°C                    |
| 6. DRIVE MODE:            | 1/32DUTY, 1/6 BIAS              |
| 7. VIEWING ANGLE:         | 6 O'CLOCK                       |
| 8. BACKLIGHT:             | 4PCS White LED,VF=5.0V; IF=60mA |
| 9. CUSTOMER PART NO.:     | BOCEN STANDARD PRODUCT          |

**BOCEN DISPLAY TECHNOLOGY CO., LTD.**

DESIGNED BY: Sylar	<b>BG16032-02</b>	VERSION: 1.0
CHECKED BY: William		NO.: 1 OF 1
APPROVED BY: Rio		UNIT: mm
Website: <a href="http://www.bocentech.com">http://www.bocentech.com</a>		DATE: 2018-03-21